
## LIGHTOLIER®

# WX4 Series Wet Location Exit **WX4**

Page 1 of 1


### LED Exit Suitable for Wet Locations and Corrosive Environments

The WX4 Series is a corrosive environment LED Exit suitable for use in wet location areas. It offers extremely low operating costs.



#### Complete Fixture consists of base exit.

#### How to Specify:




#### Features

- Illumination: Illumination of the exit face is accomplished with long lasting, high output Light Emitting Diodes (LEDs). LEDs and support electronics have an expected life of 25 years.
- **2. Housing:** Constructed of fiberglass, corrosion-resistant, grey housing. Field removable chevrons offer application flexibility.
- 3. Electronics: AC Only or Emergency Operation. Emergency Operation version provides universal 120/277 VAC operation with solid-state circuitry. Charging system is complete with low voltage disconnect, AC lockout, brownout protection, AC indicator lamp and test switch.
- Battery: Maintenance free, sealed lead calcium battery has an estimated service life of 5 years, and an operating temperature range of 65°F (19°C) to 85°F (30°C).
- 5. Warranty: Electronics: 3 years; Battery: 1 year full, 4 years pro-rata

#### **Code Compliance**

UL 924 listed for wet locations.

National Electrical Code (NEC), NFPA70 and NFPA101 life safety codes; and OSHA safety code illumination standards.



631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710 We reserve the right to change details of design, materials and finish. www.lightolier.com © 2008 Philips Group • C0308

## PHILIPS